

#### Short Specification:

The 4' Stairwell LED series are perfect solutions for general lighting applications such as corridors, stairways and walkways. This LED comes back with dual motion sensors, consuming only 33% of energy in absence of human traffic to provide further energy savings.

The motion sensors can be tilted to target the area of interest and the ON time and sensitivity can be programmed using an IR (infrared) remote control.



| MODEL              | DESCRIPTION            | WATTS                   | LUMENS | COLOR TEMP. |
|--------------------|------------------------|-------------------------|--------|-------------|
| LSD-LED-4-8/26-840 | 4' Stairwell LED at 4K | 26 (8W is standby mode) | 3,000  | 4,000K      |
| LSD-LED-4-8/26-850 | 4' Stairwell LED at 5K | 26 (8W is standby mode) | 3,000  | 5,000K      |
| LSD-R              | Remote                 |                         |        |             |

#### Applications:

- Corridors/ Hallways
- Parking Garages
- Staircases

#### Features:

- DLC listed
- Housing is electrolytic zinc coated steel with PR12 powder coating which prevents color degradation.
- Anti-rust and corrosion resistant
- Prevents unwanted entry of insects and dust
- Ample knockouts for convenient mounting with recessed or surface power feeds
- Meets ADA wall mounting requirements
- High performance driver and LED module
- Polycarbonate protective LED lens

#### Electrical:

- Operating input voltage: 120/270V, 50/60 Hz
- Electrical power consumption: 26W when fully illuminated and 8W when in standby mode
- Luminous efficacy: 115 Lm/W
- Power factor: 0.9 min.
- THD<15%
- Color temperature: 5,000K
- Operating temperature: -20° to +40°C
- CRI: >80
- 50,000 hour life rating
- 5 year limited warranty

#### Dimensions:

