



Short Specification:

Para Image™ Retrofit Frame Sets allow “instant” remodeling of unsightly old lay-in troffer lighting systems at the lowest possible cost. This retrofit system consists of three components:

1. A support frame to reposition the existing light fixture up to allow enough room to install the new louver.
2. A door frame equipped with pivot latches and positive hinging features that can be easily converted to pivot from either side.
3. A lens, diffuser, or louver. You can choose any of Louvers International’s Para Image™ Louvers or Premier Lenses.

In most cases, this system will easily install with no electrical or ceiling alterations. The Retrofit Frame Sets are offered in 1' x 4', 2' x 2' and 2' x 4' sizes to fit any existing standard grid non-air handling ceiling system.

The variety of compatible lenses, diffusers and louvers makes this system exceptionally versatile in meeting a wide range of remodeling requirements. Before placing an order, please decide which type of louver, lens or diffuser you would like and then contact your sales representative at Louvers International.

Features:

- Easy to install
- Fits most existing grid systems
- Can use with most louver types
- Very economical for remodeling

Ordering Chart:

PART NUMBER	DESCRIPTION
LI-RTF-14	1' x 4' Retrofit Grid Assembly
LI-RTF-22	2' x 2' Retrofit Grid Assembly
LI-RTF-24	2' x 4' Retrofit Grid Assembly
LI-RTF-24-095	2' x 4' Retrofit Grid Assembly (.095" Thickness with Clear Prismatic Pattern 12)
LI-RTF-24-P1	2' x 4' Retrofit Door Frame with LI-1-24-S1 Installed

