

The Rogue recessed series of fixtures was developed to deliver light where you need it, right at the task. Going back to our louvers roots, we developed a new way of utilizing LED technology with lighting louvers to deliver a unique lighting effect with no glare.

Light will appear on the areas of illumination. When you are above the 37° viewing angle, you cannot see where the light is coming from. There are no illuminated lenses to make glare or reflection spots on monitors, screens, and windows.

Standard finishes are black or white, with custom colors available. Dedicated Kelvin temperatures from 2700-6500 or select color tuning options for the same ranges. For those discerning designers we offer up to 95 CRI.

The fixture design eliminates concerns related to bug entrapment and dirt depreciation, making the Rogue just about maintenance free.

We are bringing back the louver with a cool new subdued look in all our Rogue fixtures. Light up your office, school, retail stores, and commercial spaces with a fixture that delivers on every count.

Don't forget to check out our Rogue Linear fixtures with the same down light options and additional uplight features, too.



FEATURES

- Made in USA
- Powder coated housing
- 120 - 277V and 347/480V
- 50° and 80° beam angle options
- White, Black, or Matte Black louver finishes
- 2700, 3000, 3500, 4000, and 5000 Kelvin available
- 2700 - 6500 Kelvin color tuning options
- 70, 80, 90, and 95+ CRIs available
- RGBW uplight option
- 0-10v dimming (Dim to Off available)
- Dali - 1% Dimming
- 12v Auxiliary Power available
- L70 @ 50,000
- Corner joiners for unique designs



APPLICATIONS

- Offices
- Schools
- Libraries
- Health Care

CERTIFICATIONS

- 5 year warranty
- ETL Listed
- IC Rated
- ROHS
- Prop 65
- Title 24
- Suitable for Continuous Row Rating of 9.5A or 1190W Max

OPTIONS

- 6' Flexible Metal Conduit Whip (3 wire)
- Emergency battery backup
- Daylight Harvesting sensor
- Occupancy sensor
- Wi-Fi and Bluetooth connected options



ETL CLASSIFIED



ORDERING GUIDE
EXAMPLE: RG-VT-24-40-35K-80-U-C50-MB-W

SERIES	STYLE	SIZE	WATTAGE	CCT	CRI	VOLTAGE	BEAM ANGLE
RG - Rogue	VT - Volumetric	22 - 2x2	10 - 10W	27K - 2700K	70	U - 120-277V	C30 - CLEAR 30°
	FT - Flat Bottom	24 - 2x4	20 - 20W	3K - 3000K	80		F30 - FROSTED 30°
		14 - 1x4	25 - 25W	35K - 3500K	90		C50 - CLEAR 50°
			30 - 30W	4K - 4000K	95		F50 - FROSTED 50°
			35 - 35W	5K - 5000K			C80 - CLEAR 80°
			40 - 40W	CT - COLOR TUNING			F80 - FROSTED 80°
			45 - 45W				COB4X9 - CLEAR OVAL BEAM 40° X 90°
			50 - 50W				FOB4X9 - FROSTED OVAL BEAM 40° X 90°
							CWW - CLEAR WALL WASH
			FWW - FROSTED WALL WASH				

LOUVER COLOR	FIXTURE COLOR	ACCESSORIES
WH - WHITE	W - WHITE	6SF - 6' FLEXIBLE CONDUIT WHIP
BL - BLACK	C - CUSTOM	PC - Power Cord
MB - MATTE BLACK		BLE - Bluetooth
		WIFI - WIFI
		N9 - Nimbus 9 WIFI
		EM - Emergency Battery Backup
ACC - Aircraft Cable 10ft adjustable		
		DLH - Daylight Harvesting Sensor